

# NOZZLE CHECK VALVE 150#/ PN10/16/25/40 DIN FLANGED



Fig. 4781

## Features

Design	Non slam. 1 piece up to DN250. resilient or metal seated
Rating	PN10/16/25/40, 150LB
Face to face	According to dimension table
Ends	DIN/ANSI Flanged ,

## Materials

N°	Part name	Material
1	Body	A216 WCB / A351 CF8M
2	Disc	A216 WCB / A351 CF8M
3	Seat	A351 CF8M / NBR / EPDM
4	Gasket	NBR / EPDM

## Main dimensions

DN	Size		150LB L	PN10/16/25		PN40	
	NPS			Long	Short	Long	Short
50	2"		203	203	130	267	130
65	2½"		216	216	160	292	160
80	3"		241	241	180	318	180
100	4"		292	292	200	356	200
125	5"		330	330	230	400	230
150	6"		356	356	270	444	270
200	8"		495	495	330	533	330
250	10"		622	622	370	622	370
300	12"		698	698	450	711	450
350	14"		787	787	520	838	520
400	16"		864	864	580	864	580
450	18"		978	978	650	978	650
500	20"		978	978	720	1016	720
600	24"		1295	1295	980	1346	980
700	28		1448	1448	1180	-	-
750	30		1524	-	-	-	-
900	36		1956	-	-	-	-

