

BUTTERFLY VALVE PN10/16/150# WAFER



Fig. 5762

Features

Design	Concentric disc, Resilient seated.
Rating	PN10/16/150#
Face to face	DIN 3202-K1. API 609.
Ends	WAFER DIN / ANSI

Materials

N°	Part name	Material
1	Body	A216 WCB / A351 CF8M
2	Disc	A216 WCB / SS 304 / SS 316
3	Stem	A182 F6A / A182 F316
4	Seat	NBR / EPDM / Viton

Main dimensions

Size		L	PN10		PN16		150#		H1	H2	H3
DN	NPS		D	n-ød	D	n-ød	D	n-ød			
40	1½"	33	110	4-18	110	4-18	98,5	4-16	68	139	29
50	2"	43	125	4-18	125	4-18	120,6	4-19	80	161	29
65	2½"	46	145	4-18	145	4-18	139,7	4-19	89	175	29
80	3"	46	160	4-18	160	4-18	152,4	4-19	95	181	29
100	4"	52	180	4-18	180	4-18	190,5	4-19	114	200	29
125	5"	56	210	4-18	210	4-18	215,9	4-22,4	127	213	29
150	6"	56	240	4-22	240	4-22	241,3	4-22,4	139	226	29
200	8"	60	295	4-22	295	4-22	298,4	4-22,4	175	260	35
250	10"	68	350	4-22	355	4-26	361,9	4-25,4	203	292	35
300	12"	78	400	4-22	410	4-26	431,8	4-25,4	242	337	35
350	14"	78	460	4-22	470	4-26	476,2	4-28,4	267	368	45
400	16"	102	515	4-26	525	4-30	539,7	4-28,4	297	400	51,2
450	18"	114	565	4-26	585	4-30	577,8	4-31,8	318	422	51,2
500	20"	127	620	20-26	650	20-33	635	20-31,8	348	480	64,2
600	24"	154	725	20-30	770	20-36	749,3	20-35,1	444	562	64,2

